

DATA SHEET – ACL 5B

MODELS	TENSION	POWER RATING	CONSUMPTION	AMPERE	FREQUENCY
Heated Display Case AML ACL LP 585, 5 trays	120V	504W	0.504 Kwh	4.2 A	50-60 Hz
Heated Display Case AML ACL LC 585, 5 trays	120V	504W	0.504 Kwh	4.2 A	50-60 Hz

LC = Led with matte gray / LP = Led with bright black

GENERAL FEATURES:

- > Brushed stainless steel 430/439/441, 0.5mm thick;
- > Bright stainless steel 430, 0.4mm thick trays;
- > 4mm thick tempered glass;
- > Anodized aluminum frame in matte gray or bright black;
- > Maximum energy consumption of 0.504 Kwh;
- > 500W tubular resistance;
- > Bimetal thermostat (68°F – 248°F)
- > Fiberglass wire 18 AWG max. temp. 842°F;
- > LED light 12V IP20 4.8W/M
- > Electric cable 18AWG American plug NEMA 5-15P;

SIZE	VOLUME (inner)	NET WEIGHT	PACKAGE	VOLUME (outer)	GROSS WEIGHT
30.3" x 14.2" x 13.8"	1724.52 oz	24.3 lb	32.5" x 15.8" x 16.2"	8318.7 in ³	29 lb

