

## DATA SHEET – ACL 4B

MODELS	TENSION	POWER RATING	CONSUMPTION	AMPERE	FREQUENCY
Heated Display Case AML ACL LP 584, 4 trays	120V	253W	0.253 Kwh	2.1 A	50-60 Hz
Heated Display Case AML ACL LC 584, 4 trays	120V	253W	0.253 Kwh	2.1 A	50-60 Hz

LC = Led with matte gray / LP = Led with bright black

### GENERAL FEATURES:

- > Brushed stainless steel 430/439/441, 0.5mm thick;
- > Bright stainless steel 430, 0.4mm thick trays;
- > 4mm thick tempered glass;
- > Anodized aluminum frame in matte gray or bright black;
- > Maximum energy consumption of 0.253 Kwh;
- > 250W tubular resistance;
- > Bimetal thermostat (68°F – 248°F)
- > Fiberglass wire 18 AWG max. temp. 842°F;
- > LED light 12V IP20 4.8W/M
- > Electric cable 18AWG American plug NEMA 5-15P;

SIZE	VOLUME (inner)	NET WEIGHT	PACKAGE	VOLUME (outer)	GROSS WEIGHT
24.4" x 14.2" x 13.8"	1386.37 oz	22.1 lb	26.6" x 15.8" x 16.2"	6808,536 in <sup>3</sup>	25 lb

