

DATA SHEET – 486 9B

MODEL	TENSION	POWER RATING	CONSUMPTION	AMPERE	FREQUENCY
Warmer Humidity Merchandiser display, 9 trays	120V	706W	0.706 Kwh	5.88 A	50-60 Hz
Warmer Humidity Merchandiser display SS, 9 trays	120V	706W	0.706 Kwh	5.88 A	50-60 Hz
Warmer Humidity Merchandiser display PT, 9 trays	120V	706W	0.706 Kwh	5.88 A	50-60 Hz

SS = Selv-Service / PT = Pass-Thru

GENERAL FEATURES:

- > Brushed stainless steel 439/441, 0.5mm thick and bright stainless steel 430, 1mm thick;
- > Bright stainless steel 430, 0.4mm thick trays;
- > Carbon steel nickel-plated grill;
- > 4mm thick tempered glass;
- > Anodized aluminum frame in matte gray;
- > Maximum energy consumption of 0.706 Kwh;
- > 700W tubular resistance;
- > Capillary thermostat (86°F - 203°F);
- > Analog thermometer;
- > Fiberglass wire 18 AWG max. temp. 842°F;
- > LED light 12V IP20 4.8W/M;
- > Electric cable 18AWG American plug NEMA 5-15P;

SIZE	VOLUME (inner)	NET WEIGHT	PACKAGE	VOLUME (outer)	GROSS WEIGHT
18" x 17.5" x 32.7"	2874.19 oz	46.3 lb	20.3" x 19.3" x 35.9"	14065.261 in ³	51 lb

