

## DATA SHEET – CALIOPE 4BD

MODELS	TENSION	POWER RATING	CONSUMPTION	AMPERE	FREQUENCY
Heated Display Case AML CALIOPE LP 4BD, 4 trays	120V	506W	0.506 Kwh	4.2 A	50-60 Hz
Heated Display Case AML CALIOPE LC 4BD, 4 trays	120V	506W	0.506 Kwh	4.2 A	50-60 Hz

LC = Led with matte gray / LP = Led with bright black

### GENERAL FEATURES:

- > Brushed stainless steel 439/441, 0.5mm thick;
- > Brushed stainless steel 439, 0.5mm thick trays;
- > 4mm and 6mm thick tempered glass;
- > Anodized aluminum frame in matte gray or bright black;
- > Maximum energy consumption of 0.506 Kwh;
- > 500W tubular resistance;
- > Bimetal thermostat (68°F – 248°F)
- > Fiberglass wire 18 AWG max. temp. 842°F;
- > LED light 12V IP20 4.8W/M
- > Electric cable 18AWG American plug NEMA 5-15P;

SIZE	VOLUME (inner)	NET WEIGHT	PACKAGE	VOLUME (outer)	GROSS WEIGHT
22.5" x 17.7" x 19.7"	2197,91 oz	35.3 lb	24.6" x 19.5" x 21.7"	10409.49 in <sup>3</sup>	40 lb

